## **DECLARATION OF PERFORMANCE**

SalzMII-CRP-2018/03/28-GB



**PRODUCT** 

**Product type** Slow heat release appliance

Type designation Salzburg M II

**Product identification** See product instruction manual

Intended area of use Heating of rooms in residential buildings

**Fuel** Wood

**MANUFACTURER** 

Name Nordpeis AS

Adress Gjellebekkstubben 11

3420 Lierskogen, Norway

**CHECKS** 

According to AVCPSystem 3StandardEN 15250:2007

**Test institute** Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625

has checked declared performance and issued test report no. RRF- 50 11 2758-1 / RRF- 50 14 3624

## **DECLARED PERFORMANCE**

				Harmonized
Essential Characteristic Performance		nce	technical	
				specification
Reaction to fire	A1			
Minimum distances to combustible material	50/150	mm rear		
	100	mm side		
other safety distances according product manu-				
		product ma		
Risk of falling embers	Approved			
Emission from combustion:				
Carbon monoxide at 13% O <sub>2</sub>	CO =	0,095	% Vol	
Oxygen nitride NOx at 13% O <sub>2</sub>	NOx =	142	$mg/m^3$	
Organic Gaseous Carbon at 13% O <sub>2</sub>	OGC =	81	$mg/m^3$	
Particulate Matter at 13 O <sub>2</sub>	PM =	32	mg/m³	EN 15250:2007
Surface temperatures	Approved			
Cleanability	Approved		_	
Mechanical durablity	Approved			
Releases of Hazardous Substances	Approved			_
Total thermal output		39,4	kWh	
Nominal output after elapsed time at 25% of max. mean temperature	P =	2,40	kW	
Flue gas temperature at nominal output	t <sub>a</sub> =	157	°C	
Energy efficiency	η=	84,0	%	

The udersigned is responsible for the manufacture and conformity with declared performance

Stian Varre, CEO Nordpeis AS